

New Launch In 2023



10-Port USB 3.2 Gen1 PD Charging Hub

USB-C1030PD

- ▶ Supports iOS, Android devices and MacBook Air, MacBook Pro or Chromebook.
- ▶ Supports USB PD 2.0 / USB PD 3.0 (PPS) / USB Battery Charging Spec 1.2 at Sync & Charge mode.
- ▶ Enables to deliver output current of each port up to 27W; supports 5V 3A / 9V 3A / 12V 2.25A / 15V 1.8A either at SYNC mode or Charge mode on each port.
- ▶ Supports Over Current Protection, Over Temperature Protection, and Short Circuit Protection on each port.



20-Port USB 3.2 Gen1 PD Charging Hub

USB-C2030PD

- ▶ Supports iOS, Android devices and MacBook Air, MacBook Pro or Chromebook.
- ▶ Supports USB PD 2.0 / USB PD 3.0 (PPS) / USB Battery Charging Spec 1.2 at Sync & Charge mode.
- ▶ Enables to deliver output current of each port up to 27W; supports 5V 3A / 9V 3A / 12V 2.25A / 15V 1.8A either at SYNC mode or Charge mode on each port.
- ▶ Supports Over Current Protection, Over Temperature Protection, and Short Circuit Protection on each port.



USB 2.0 12-Port Type C Hi-Power Charging Hub

USB-2012TC

- ▶ Supports iOS, Android devices and MacBook Air, MacBook Pro or Chromebook.
- ▶ Enables to provide up to 5V 3A output current on each port.
- ▶ Supports Over-Current Protection & Short Circuit Protection on each port.
- ▶ Supports $\pm 15\text{kV}$ (air), $\pm 8\text{kV}$ (contact) ESD protection on each port.



USB 2.0 20-Port Type C Smart Charging Hub

USB-2020TC

- ▶ Supports iOS, Android devices and MacBook Air, MacBook Pro or Chromebook.
- ▶ Enables to provide up to 3A by 12 ports / 1.5A by 8 ports or 2.4A by 20 ports at B/C 1.2 charging output current on each port.
- ▶ Supports Over-Current Protection & Short Circuit Protection on each port.



USB 2.0 10-Port Hi-Power Charging Hub

USB-1024BC

- ▶ Enables to provide up to 1.5A at Sync (CDP mode) or 2.4A at Charge (DCP mode) output current on each port.
- ▶ Supports the iOS, Android devices.
- ▶ Enables Green Energy function automatically shutdown the hub when all devices are fully charged at Charge mode.



USB 2.0 20-Port Hi-Power Charging Hub

USB-2024BC

- ▶ Enables to provide up to 1.5A at Sync (CDP mode) or 2.4A at Charge (DCP mode) output current on each port.
- ▶ Supports the iOS, Android devices.
- ▶ Enables Green Energy function automatically shutdown the hub when all devices are fully charged at Charge mode.



8K DisplayPort 1.4 Repeater

DP-14R

- ▶ Supports UHD resolutions up to 7680 X 4320 @60Hz & 3840 X 2160 @144Hz 4:2:2 10bit.
- ▶ Fully compliant with DisplayPort specification 1.4 HBR3, HDCP 2.3, HDR, DPCP.
- ▶ Supports 8k @60Hz and 4K @144Hz, max. length: 2m in; 10m out.
- ▶ Enables cascading 5 levels at 4K @144Hz.



USB 2.0 Isolator

USB-ISO11HS

- ▶ Supports USB isolation 5000VDC between USB host and USB device.
- ▶ USB 2.0 compatible, 1.5 / 12 and 480Mbps high speed Bi-directional communication.
- ▶ Isolated host power through a DC-to-DC converter can provide 5V 300mA to your USB device.



Isolated USB 3.2 Gen2 4-Port Hub

USB3-GEN2iH

- ▶ Isolation 2000VDC between USB host and USB devices.
- ▶ Supports USB 3.2 Gen2 data transfer rates up to 10 Gbps.
- ▶ The USB 3.2 Gen2 Type-C ports comply with USB Battery Charging Spec 1.2; and enable to provide up to 1.5A (CDP mode) output current on each port.



4:2 8K DisplayPort 1.4 Switch

DP-14S

- ▶ Supports UHD resolutions up to 7680 X 4320 @60Hz & 3840 X 2160 @144Hz 4:2:2 10bit.
- ▶ Supports 8K @60Hz (max. length: 2m in; 10m out at 2 DP in); 4K @144Hz (max. length: 2m in; 10m out at 1 DP in).
- ▶ Fully compliant with DisplayPort 1.4 HBR3, HDCP 2.3, HDR, DPCP.



Isolated USB 2.0 4-Port Hub

USB-ISO204

- ▶ Supports USB isolation 5000VDC between USB host and USB device.
- ▶ USB 2.0 compatible, 1.5 / 12 and 480Mbps high speed Bi-directional communication.
- ▶ Supports ± 15 kV ESD protection.



2-Port USB 3.2 Gen1 8K DisplayPort KVM Switch

KVM-U3DP-V1

- ▶ Fully compliant with DisplayPort 1.4 HBR3, HDCP 2.3, HDR, DPCP; Supports DisplayPort Dual Mode (DP++) for direct output single-link DVI or HDMI signals via a powered DisplayPort-to-HDMI/DVI adaptor.
- ▶ Supports UHD resolutions up to 7680 X 4320 @60Hz & 3840 X 2160 @144Hz 4:2:2 10bit, max. length: 2m in; 10m out.
- ▶ Hosts selectable by Port selection pushbutton or hotkey.



Chipset Communication Co.,Ltd.

ADD 5F-3, No. 130 Jiankang Rd., Zhonghe Dist., New Taipei City 23585, Taiwan, R.O.C.

TEL +886-2-2222 8837 **FAX** +886-2-2225 2564

E-mail sales@chipsetcomm.com.tw